[va-Q-one 23 Dry Ice]

For -70 °C shipments





Product picture shows an exemplary solution for the temperature range +2 °C to +8 °C

## **DESCRIPTION**

Specifically designed for door-to-door pharmaceutical distribution of smaller volumes to remote locations, OnePak ensures your products reach even the most inaccessible areas without compromising quality or efficacy. This single-use solution is ideal for regions with limited logistics services, eliminating the need for return shipping and ensuring consistent access to medicines.

Date: 2025-01-31 Page: 1 of 2 Version: 15322

# OnePak 23 Dry Ice (Article number: BC000352 + EK002351)

[va-Q-one 23 Dry Ice]

For -70 °C shipments



#### **DIMENSIONS AND WEIGHT**

External Dimensions (1 x w x h)		Internal Dimensions <sup>1</sup> (l x w x h)		Tolerances	
[ mm ]	[inch]	[ mm ]	[inch]	[ mm ]	[inch]
480 x 460 x 385	18.9 x 18.1 x 15.2	255 x 255 x 185	10 x 10 x 7.3	± 5	± 0.2

Tare W	eight <sup>1</sup>	Payload <sup>1</sup> (Volume)	
[kg]	[lbs]	[L]	
17.5 ± 1	38.6 ± 2.2	12	

<sup>1</sup>including Dry Ice

#### DRY ICE CONFIGURATION

Dry Ice compartment	Dry Ice pellet diameter		Weight		
	[mm]	[inch]	[kg]	[lbs]	
Upper compartment	3	0.1	5.5	12.1	
Side compartments	3	0.1	7.5	16.5	

### PERFORMANCE The OnePak 23 Dry Ice is qualified in the temperature range below -60 °C

Temperature scenario	Duration [hrs]	Kelvin-hours <sup>2</sup>	Average ambient temperature [°C]
ISTA 7D summer	≥ 104	≥ 10389	+29.9

 $<sup>^2\</sup>mbox{Detailed}$  information about the concept of Kelvin-hours on www.kelvinhours.com

For more details, please view the qualification report. Before performing a shipment with the OnePak 23 Dry Ice it is suggested that the user performs a validation process with the equipment available and under the conditions available. A test in worst case conditions is recommended. The box provides a very stable and well-designed system solution which has to be adapted on the particular requirements of the user.

For more information please contact support@envirotainer.com.

Date: 2025-01-31 Page: 2 of 2 Version: 15322