[va-Q-case 1/2 Euro -37G] For -40 °C shipments





DESCRIPTION

Delivering superior performance while streamlining handling, the ProofTainer family features six sizes, accommodating from 0.5 – 2 EU or 1 - 2 US pallets. Whether you're shipping clinical trials or commercial drugs, we ensure consistent temperature control throughout your products journey. With qualified temperature ranges from -70°C to +20°C and over 120 hours of autonomy, ProofTainer provides optimal conditions for your sensitive cargo, delivering the flexibility you need for your product requirements.

DIMENSIONS AND WEIGHT

External Dimensions (l x w x h)			Internal Dimensi)	Tolerances		
[mm]	[inch]		[mm]	[inch]	[m	m]	[inch]
800 x 600 x 8	300 31.5 × 23	.6 x 31.5	610 x 356 x 470	24 x 14 x 18	.5 ±	5	± 0.2
Tare Weight ¹ Vo		Volun	netric weight	Maximum Payl	oad (Weight)	Payload ¹ (Volume)	
[kg]	[lbs]	[kg]	[lbs]	[kg]	[lbs]		[L]
153 ± 15	337.3 ± 33.1	64	141.1	100	220.5		96

¹including Temperature Batteries

TEMPERATURE BATTERY CONFIGURATION

ProofBlok	Pieces	Dimensions [mm]	s ² (l x w x h) [inch]	Weight [kg] [lbs]		Material number
27L -37G	18	470 x 275 x 32	18.5 x 10.8 x 1.3	5.3	11.7	AK000296

²dimensions of empty Temperature Battery shell, variation due to PCM inside and aggregation state possible

PERFORMANCE The ProofTainer Case -37G is qualified in the temperature range from -40 °C to -20 °C

Temperature scenario	Duration [hrs]	Kelvin-hours ³	Average ambient temperature [°C]	
controlled summer	> 120	≥ 6564	+19.7	
extreme summer	> 120	n.a.	+49.8	

³Detailed information about the concept of Kelvin-hours on www.kelvinhours.com

For more details, please view the qualification report. Before performing a shipment with the ProofTainer Case -37G it is suggested that the user performs a validation process with the equipment available and under the conditions available. A test in worst case conditions is recommended. The box provides a very stable and well-designed system solution which has to be adapted on the particular requirements of the user.

For more information please contact support@envirotainer.com.